



Amerex Corporation

RUGGED

- 6 Year Warranty
- Stored Pressure Design
- Dependable Drawn Steel Cylinders
- Durable High Gloss Polyester Powder Paint
- All Metal Valve Construction
- Temperature Range -65°F to 120°F

USER FRIENDLY

- Easy and More Economical to Maintain and Service
- Large Loop Pull Pin
- Bar Coded and Bi-lingual Labels

OPTION

- USCG Approved with Bracket Listed on UL Label



Aluminum Valve
 A620T
 B403/T
 B409T
 B453
 B457
 A412



Brass Valve
 B462
 B447
 408



Available in Wheeled and Stationary Extinguishers

REGULAR extinguishers contain a siliconized sodium bicarbonate based dry chemical with free flowing and non-caking additives. Economical Class B & C protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gases and will not conduct electricity back to the operator.

Largest selection of size and extinguisher options available

AGENT TYPE	REGULAR DRY CHEMICAL									
VALVE TYPE	ANODIZED ALUMINUM					CHROME PLATED BRASS				
DESIGN	NOZZLE			HOSE & NOZZLE						
MODEL NUMBER	A620T	B403/B403T	B409T	B453	B457	A412	B462	B447	408	
UL & ULC RATING	2B:C	10B:C	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C	120B:C	
CAPACITY (LBS.)	1	2.5	5	5.5	10	20	6	10	20	
SHIPPING WT. (LBS.)	2.5	5.5	9.25	9.75	18	38	13.75	19	39	
HEIGHT (IN.)	10	15.5	15.25	15.25	20	24	16.25	20.25	24	
WIDTH (IN.)	3.5	5.75	5.5	7.25	7.75	10.25	8.5	8.75	10.25	
DEPTH (IN.)	2.63	3	4.25	4.25	5	7	5	5	7	
RANGE (INITIAL- FT)	5-8	9-15	12-18	12-18	15-21	15-21	15-21	15-21	15-21	
DISCHARGE TIME (SEC.)	10	10	10	14	18	28	14	18	28	
FM APPROVED		YES	YES	YES	YES	YES	YES	YES	YES	
OPTIONAL CHROME CYLINDER	YES	YES	YES	YES	YES		YES	YES		
INCLUDED BRACKET	VEHICLE	WALL/VEHICLE	VEHICLE	WALL						

Manufactured and Tested to ANSI/UL Standards
 Complies with NFPA 10 Standard
 ISO-9001 / ISO-14001 Certified
 UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - ANSI/UL299 &
 CAN/ULC-S508 - ANSI/UL711

MADE IN U.S.A.

REGULAR DRY CHEMICAL